

TOYOTOMI

KEROSENE COOKING / HEATING STOVE Model K-30F

FEATURES

■ MULTIPLE FUNCTION

K-30F is designed as cooking purpose mainly. Due to powerful 2.25 kW heating power, it is easy to cook as well as boiling the water. Furthermore, it can be used as a space heating in the house.

■ CLEAN COMBUSTION

The TOYOTOMI's state of the art Clean Chamber System maximizes fuel combustion and reduces carbon monoxide (CO) and other unwanted emission gases to very safety level.

■ DURABLE GLASS FIBER WICK

Durable Glass Fiber Wick ensures a longer wick life-time than the cotton wick. The Wick cannot be burned out easily even if the stove runs out the fuel. Tar deposit on the wick can be removed cleanly by the method of burning dry.

■ DOUBLE WALL TANK CONSTRUCTION

The double wall tank construction prevents fuel leakage even when stove tips over for safety.

■ EASY TO OPERATE AND MAINTAINANCE

Just turn the knob clockwise and ignite with a match or a lighter. Then turn the knob counterclockwise for turn off. No tool is required to replace a wick and it is easy for maintenance.

■ ADJUSTABLE HEATING POWER

20% of the heating power is adjustable by handle.

■ VERSATILE

Compact and light weight so you can take your stove anywhere.

■ MADE IN JAPAN

TOYOTOMI kerosene heaters are produced by our own factories in Japan.



SPECIFICATIONS

MODEL:	K-30F
HEATING CAPACITY:	7,600 BTU/h (2.25 kW/h) - 6,100 BTU/h (1.80 kW/h)
FUEL CONSUMPTION:	0.209 L/h - 0.168 L/h
TANK CAPACITY:	4.0 L
BURNING TIME:	Approx. 19 - 23 hrs.
HEATER DIMENSIONS (WxDxH):	343 x 343 x 315 mm
CARTON DIMENSIONS (WxDxH):	380 x 380 x 340 mm
NET / GROSS WEIGHT:	Approx. 3.5 / 4.6 kg
CONTAINER Q'TY (20 / 40 / 40HC):	540 / 1116 / 1302 units

TOYOTOMI CO., LTD.

5-17, MOMOZONO-CHO, MIZUHO-KU,
NAGOYA, 467-0855 JAPAN
TEL : 81-52-822-1108, FAX : 81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

Printed in Japan
Subject to change with or without notice